



## China 6202 Bearing Supplier



### 6012 2RS Zz SKF/NACHI/NTN/NSK/NACHI/Koyo Interchange Bearing

Bearing No. 6012

6012 Bearing 2D drawings and 3D CAD models

Size	60x95x18 mm
Bore Diameter	60 mm
Outer Diameter	95 mm
Width	18 mm
d	60 mm
D	95 mm
B	18 mm
C	18 mm
r min.	1.1 mm
da min.	66 mm
Da max.	89 mm
ra max.	1.0 mm
Weight	0.418 Kg
Basic dynamic load rating (C)	29,4 kN
Basic static load rating (C0)	23,2 kN
(Grease) Lubrication Speed	7000 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NACHI
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0



## China 6202 Bearing Supplier

Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	60MM Bore; 95MM Outside Diameter; 18MM Outer Race Width; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Other Features	Deep Groove
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.nachiamerica.com">http://www.nachiamerica.com</a>
Bore	2.362 Inch   60 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	0.709 Inch   18 Millimeter
Outside Diameter	3.74 Inch   95 Millimeter
Bore Type	Cylindrical Bore
Configuration	Single Row
Bore Size	60 mm
Width	18 mm
Fillet Radius/Chamfer	1.1 mm
Dynamic Load Rating	29,400 N



## China 6202 Bearing Supplier

Static Load Rating	23,200 N
Limiting Speed - Grease	7,100 rpm
Limiting Speed - Oil	8,500 rpm
Factor $f_0$	15.5
Radial Clearance	0.008 to 0.028 mm
$d_a$ (min)	66 mm
$D_a$ (max)	89 mm
$r_a$ (max)	1 mm